











TORCH SPECIFICATIONS

	Type	Part No.	Torch Lead Length	Current Rating	Coolant Requirements	Torch Dimensions						
						A	B	C	D	E		
		PWH-2A 70°	2-2100 (H) 2-2104 (H)	12.5 ft. 25 ft.	75 Amps (DCSP)	2,000 BTU/hr (504 K/Cal/hr) 1/4 gpm coolant flow @ 50 PSI (0.9 lpm @ 3.7 kg/cm ²)	7-15/16" (202 mm)	1-11/16" (43 mm)	5/8" (16 mm)	7/8" (22 mm)		
		PWH-2A 90°	2-2101 (H) 2-2105 (H)	12.5 ft. 25 ft.			7-3/4" (196 mm)	1-11/16" (43 mm)	5/8" (16 mm)	7/8" (22 mm)		
		PWM-2A 180° Offset	2-2102 (H) 2-2103 (M)	12.5 ft.			18-1/4" (463 mm)	13/16" (21 mm)	Min. 7-1/8" (181 mm)	Max. 15" (381 mm)	1-3/8" (35 mm)	
			2-2106 (H) 2-2107 (M)	25 ft.								
		PWH-3A 70°	2-2110 (H) 2-2114 (H)	12.5 ft. 25 ft.	150 Amps (DCSP)	6,000 BTU/hr (1513 K/Cal/hr) 1/3 gpm coolant flow @ 50 PSI (1.25 lpm @ 3.7 kg/cm ²)	8-3/4" (222 mm)	2-5/8" (67 mm)	7/8" (22 mm)	1-1/16" (27 mm)		
		PWH-3A 90°	2-2111 (H) 2-2115 (H)	12.5 ft. 25 ft.			8-1/2" (216 mm)	2-5/8" (67 mm)	7/8" (22 mm)	1-1/16" (27 mm)		
		PWM-3A 180° Offset	2-2112 (H) 2-2113 (M)	12.5 ft.			19-1/4" (489 mm)	1" (25 mm)	Min. 9-1/4" (235 mm)	Max. 16-3/4" (425 mm)	1-3/8" (35 mm)	
			2-2116 (H) 2-2117 (M)	25 ft.								
		PWH-4A 70°	2-2120 (H) 2-2125 (H)	12.5 ft. 25 ft.	200 Amps (DCSP)	8,000 BTU/hr (2017 K/Cal/hr) 1/2 gpm coolant flow @ 50 PSI (1.9 lpm @ 3.7 kg/cm ²)	12-1/2" (318 mm)	3-3/16" (81 mm)	1-1/4" (32 mm)	1-3/8" (35 mm)		
		PWH-4A 90°	2-2119 (H) 2-2126 (H)	12.5 ft. 25 ft.			12-1/4" (311 mm)	3-3/16" (81 mm)	1-1/4" (32 mm)	1-3/8" (35 mm)		
		PWM-4A 180° Offset	2-2121 (H) 2-2122 (M)	12.5 ft.			18" (457 mm)	1-3/4" (44 mm)	Min. 8-1/4" (209 mm)	Max. 16" (406 mm)	1-3/8" (35 mm)	1-1/4" (32 mm)
			2-2127 (H) 2-2128 (M)	25 ft.								
PWM-4A1 180° Inline	2-2123 (H) 2-2124 (M)	12.5 ft.	21" (53 mm)	1-3/4" (44 mm)	Min. 11-1/4" (286 mm)	Max. 19" (483 mm)	1-3/8" (35 mm)	1-1/4" (32 mm)				
	2-2129 (H) 2-2130 (M)	25 ft.										



NOTE: All torches listed incorporate a quick disconnect connector specifically for operation with the Ultima 150.