

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 1 of 16

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

CIGWELD COMWELD CRMO1, COMWELD CRMO2

SYNONYMS

"Product Code: 321379, 321383", "gas tungsten arc-welding (GTAW) special alloy steel rods"

PRODUCT USE

Filler rod for Gas Tungsten Arc- Welding of creep- resistant steels.

SUPPLIER

Company: CIGWELD Pty Ltd
Address:
71 Gower Street
Preston
VIC 3072
AUS
Telephone: (03) 9474 7400
Telephone: 1300 654 674
Emergency Tel: (03) 9474 7400

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Danger of cumulative effects.

SAFETY

Take off immediately all contaminated clothing.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
Copper coated rod comprising		
chromium	7440-47-3	1.0-2.6^
manganese	7439-96-5	1.0-1.2^
silicon powder amorphous	7440-21-3	0.6-0.8^
molybdenum	7439-98-7	0.5-1.0^
copper	7440-50-8	<0.15^
carbon, non- activated	7440-44-0	0.1^
iron	7439-89-6	balance^
which upon use, generates:		
welding fumes	Not avail.	
as		
manganese fume	7439-96-5	
molybdenum fume	7439-98-7	
iron oxide fume	1309-37-1	>60

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 2 of 16

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

chromium fume	7440-47-3
copper fume	7440-50-8
The action of the arc produces:	
ozone	10028-15-6
nitrogen oxides	Mixture

Section 4 - FIRST AID MEASURES

SWALLOWED

Not normally a hazard due to physical form of product.

EYE

- Particulate bodies from welding spatter may be removed carefully.
- DO NOT attempt to remove particles attached to or embedded in eye.
- Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye.
- Seek urgent medical assistance, or transport to hospital.

SKIN

In case of burns:

- Quickly immerse affected area in cold running water for 10 to 15 minutes.
- Bandage lightly with a sterile dressing. Treat for shock if required.
- Lay patient down. Keep warm and rested.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Copper, magnesium, aluminium, antimony, iron, manganese, nickel, zinc (and their compounds) in welding, brazing, galvanising or smelting operations all give rise to thermally produced particulates of smaller dimension than may be produced if the metals are divided mechanically. Where insufficient ventilation or respiratory protection is available these particulates may produce "metal fume fever" in workers from an acute or long term exposure.

- Onset occurs in 4-6 hours generally on the evening following exposure. Tolerance develops in workers but may be lost over the weekend. (Monday Morning Fever)
- Pulmonary function tests may indicate reduced lung volumes, small airway obstruction and decreased carbon monoxide diffusing capacity but these abnormalities resolve after several months.
- Although mildly elevated urinary levels of heavy metal may occur they do not correlate with clinical effects.
- The general approach to treatment is recognition of the disease, supportive care and prevention of exposure.
- Seriously symptomatic patients should receive chest x-rays, have arterial blood gases determined and be observed for the development of tracheobronchitis and pulmonary edema. [Ellenhorn and Barceloux: Medical Toxicology].

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 3 of 16

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk, however containers may burn.
- In a fire may decompose on heating and produce toxic / corrosive fumes.

FIRE INCOMPATIBILITY

Welding electrodes should not be allowed to come into contact with strong acids or other substances which are corrosive to metals.

HAZCHEM: None

Personal Protective Equipment

Gas tight chemical resistant suit.
Limit exposure duration to 1 BA set30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Clean up all spills immediately.
Avoid contact with skin and eyes.
Wear impervious gloves and safety glasses.
Use dry clean up procedures and avoid generating dust.
Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment if risk of overexposure exists.
- Prevent, by any means available, spillage from entering drains or water courses.
- Contain spill/secure load if safe to do so.
- Bundle/collect recoverable product and label for recycling.
- Collect remaining product and place in appropriate containers for disposal.
- Clean up/sweep up area. Water may be required.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 4 of 16

Section 6 - ACCIDENTAL RELEASE MEASURES

for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

chromium	250 mg/m ³
manganese	500 mg/m ³
molybdenum	500 mg/m ³
iron oxide fume	500 mg/m ³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

chromium	2.5 mg/m ³
manganese	5 mg/m ³
molybdenum	50 mg/m ³
iron oxide fume	25 mg/m ³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

chromium	1.5 mg/m ³
manganese	3 mg/m ³
molybdenum	30 mg/m ³
iron oxide fume	15 mg/m ³

The threshold concentration below which most people will experience no appreciable risk of health effects:

chromium	1 mg/m ³
manganese	0.2 mg/m ³
molybdenum	10 mg/m ³
iron oxide fume	10 mg/m ³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 5 of 16
Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

Multi-wall paper container NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.

STORAGE INCOMPATIBILITY

Segregate from strong acids.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC
Australia Exposure Standards	manganese fume (Manganese, fume (as Mn))		1		3			
Australia Exposure Standards	manganese fume (Manganese, dust & compounds (as Mn))		1					
Australia Exposure Standards	molybdenum fume (Molybdenum, insoluble compounds (as Mo))		10					
Australia Exposure Standards	iron oxide fume (Iron oxide fume (Fe ₂ O ₃) (as Fe))		5					
Australia Exposure Standards	iron oxide fume (Inspirable dust (Not specified))		10					
Australia Exposure Standards	chromium fume (Chromium (metal))		0.5					
Australia Exposure Standards	chromium fume (Chromium (III) compounds (as Cr))		0.5					
Australia Exposure Standards	copper fume (Copper, dusts & mists (as Cu))		1					
Australia Exposure Standards	copper fume (Copper (fume))		0.2					
Australia Exposure Standards	ozone (Ozone)					0.1	0.2	

The following materials had no OELs on our record under the following CAS

- manganese fume: CAS:7439-96-5
- molybdenum fume: CAS:7439-98-7
- copper fume: CAS:7440-50-8
- nitrogen oxides:

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 6 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
manganese fume	500	
molybdenum fume	5, 000	
iron oxide fume	2, 500	
chromium fume	250	
copper fume	100	
ozone		5

ODOUR SAFETY FACTOR (OSF)

OSF=0.00025 (welding fumes)

None assigned. Refer to individual constituents.

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

INGREDIENT DATA

WELDING FUMES:

In addition to complying with any individual exposure standards for specific contaminants, where current manual welding processes are used, the fume concentration inside the welder's helmet should not exceed 5 mg/m3, when collected in accordance with the appropriate standard (AS 3640, for example).

ES* TWA: 5 mg/m3

TLV* TWA: 5 mg/m3, B2 (a substance of variable composition)

OES* TWA: 5 mg/m3

Most welding, even with primitive ventilation, does not produce exposures inside the welding helmet above 5 mg/m3. That which does should be controlled (ACGIH). Inspirable dust concentrations in a workers breathing zone shall be collected and measured in accordance with AS 3640, for example. Metal content can be analytically determined by OSHA Method ID25 (ICP-AES) after total digestion of filters and dissolution of captured metals. Sampling of the Respirable Dust fraction requires cyclone separator devices (elutriators) and procedures to comply with AS 2985 (for example).

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 7 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

For each of the following

MANGANESE FUME:

IRON OXIDE FUME:

CHROMIUM FUME:

COPPER FUME:

Not available

MOLYBDENUM FUME:

An increased incidence of non-specific symptoms including headache, weakness, fatigue, anorexia and joint and muscle weakness has been reported to occur in mining and metallurgy workers exposed to 60-600 mg (as Mo). Some investigators have attributed gout and elevated uric acid concentration found in some Armenians to result from exposures to Armenian soils rich in molybdenum, whilst exposure has been implicated as a cause of bone disease amongst Indians. "These involvements are speculative". [US National Research Council]. As far as it is known, the recommended TLV-TWA incorporates a large margin of safety against potential pulmonary or systemic effects.

OZONE:

NOTE: Detector tubes for ozone, measuring in excess of 0.05 ppm, are commercially available.

Exposure at 0.2 ppm appears to produce mild acute but not cumulative effects. It is thought that exposures of the order of 0.1 ppm will be tolerated by most workers including asthmatics. Chronic exposure at 0.1 ppm or more can induce significant adverse effects in the lower respiratory tract of both normal and atopic individuals.

Human exposure for 2 hours at an average concentration of 1.5 ppm ozone resulted in a 20% reduction in timed vital capacity of the lung and other effects. Concentrations of ozone in excess of a few tenths ppm cause occasional discomfort to exposed individuals manifest as headache, dryness of the throat and mucous membranes of the eyes and nose following exposures of short duration.

Exposure to ozone during moderate to heavy work loads results in significantly decreased forced vital capacity (FVC) and forced expiratory volume in one second (FEV1) at 0.12 ppm; this effect is greater at higher concentrations.

NITROGEN OXIDES:

Data for nitrogen dioxide:

TLV TWA: 3 ppm 6 mg/m³ STEL: 5 ppm 10 mg/m³

ES TWA: 3 ppm 5.6 mg/m³ STEL: 5 ppm 9.4 mg/m³

IDLH Level: 50 ppm

NOTE: Detector tubes for nitrogen dioxide, measuring in excess of 0.5 ppm, are commercially available.

PERSONAL PROTECTION

EYE

Welding helmet with suitable filter. Welding hand shield with suitable filter.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

For most open welding/brazing operations, goggles, even with appropriate filters, will

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 8 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

not afford sufficient facial protection for operators. Where possible use welding helmets or handshields corresponding to AS 1336 and AS 1338 which provide the maximum possible facial protection from flying particles and fragments. [WRIA-WTIA Technical Note 7].

HANDS/FEET

Welding Gloves

Safety footwear.

OTHER

Overalls.

- Eyewash unit.

Aprons, sleeves, shoulder covers, leggings or spats of pliable flame resistant leather or other suitable materials may also be required in positions where these areas of the body will encounter hot metal.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	BE- AUS P-	-
1000	50	-	BE- AUS P-
5000	50	Airline *	-
5000	100	-	BE- 2 P-
10000	100	-	BE- 3 P-
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- For gas tungsten arc welding operations the nature of ventilation is determined by the location of the work. For outdoor work, natural ventilation is generally sufficient.

- For indoor work, conducted in either open or limited spaces, use mechanical (general exhaust or plenum) ventilation. (Open work spaces exceed 300 cubic metres per welder)

- For work conducted in confined spaces, mechanical ventilation, using local exhaust systems, is required. (In confined spaces always check that oxygen has not been depleted by excessive rusting of steel or snowflake corrosion of aluminium)

Mechanical or local exhaust ventilation may not be required where the process working time does not exceed 24 mins. (in an 8 hr. shift) provided the work is intermittent (a maximum of 5 mins. every hour). Local exhaust systems must be designed to provide a minimum capture velocity at the fume source, away from the worker, of 0.5 metre/sec.

If risk of inhalation or overexposure exists, wear SAA approved respirator or work in fume hood.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Comweld CrMo1 - Copper- coated rod with an orange tip. Comweld CrMo2 - Copper coated rod

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet
Issue Date: 31-Oct-2006
NC317ECP

CHEMWATCH 46931
Revision No:2
CD 2006/3 Page 9 of 16

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

with a black tip.

PHYSICAL PROPERTIES

Does not mix with water.
Sinks in water.

Molecular Weight: Not Applicable
Melting Range (°C): 1515
Solubility in water (g/L): Immiscible
pH (1% solution): Not Applicable
Volatile Component (%vol): Not Applicable
Relative Vapour Density (air=1): Not available.
Lower Explosive Limit (%): Not Applicable
Autoignition Temp (°C): Not Applicable
State: Manufactured

Boiling Range (°C): Not Applicable
Specific Gravity (water=1): 7.9
pH (as supplied): Not Applicable
Vapour Pressure (kPa): Not Applicable
Evaporation Rate: Not Applicable
Flash Point (°C): Not Applicable
Upper Explosive Limit (%): Not Applicable
Decomposition Temp (°C): Not Available
Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Not normally a hazard due to physical form of product.

EYE

Fumes from welding/brazing operations may be irritating to the eyes.

SKIN

Skin contact does not normally present a hazard, though it is always possible that occasionally individuals may be found who react to substances usually regarded as inert.

INHALED

Fumes evolved during welding operations may be irritating to the upper-respiratory tract and may be harmful if inhaled.

Harmful levels of ozone may be found when working in confined spaces. Symptoms of exposure include irritation of the upper membranes of the respiratory tract and lungs as well as pulmonary (lung) changes including irritation, accumulation of fluid (congestion and oedema) and in some cases haemorrhage. Exposure may aggravate any pre-existing lung condition such as bronchitis, asthma or emphysema.

CHRONIC HEALTH EFFECTS

Principal routes of exposure include accidental contact with the molten metal and inhalation of fume arising as a consequence of the action of the flame on the rod / wire. Although fume generation rates are generally low, excessive heating of the material, well above its quoted melting point, may result in over-exposure. Welding fume with high levels of ferrous materials may lead to particle deposition in the lungs (siderosis) after long exposure. This clears up when exposure stops. Chronic

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 10 of 16

Section 11 - TOXICOLOGICAL INFORMATION

exposure to iron dusts may lead to eye disorders.

Exposure to fume containing high concentrations of water-soluble chromium (VI) during the welding of stainless steels in confined spaces has been reported to result in chronic chrome intoxication, dermatitis and asthma. Certain insoluble chromium (VI) compounds have been named as carcinogens (by the ACGIH) in other work environments. Chromium may also appear in welding fumes as Cr₂O₃ or double oxides with iron. These chromium (III) compounds are generally biologically inert.

Ozone is suspected to produce lung cancer in laboratory animals; no reports of this effect have been documented in exposed human populations.

Other welding process exposures can arise from radiant energy UV flash burns, thermal burns or electric shock

The welding arc emits ultraviolet radiation at wavelengths that have the potential to produce skin tumours in animals and in over-exposed individuals, however, no confirmatory studies of this effect in welders have been reported.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

WELDING FUMES:

Not available. Refer to individual constituents.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

MANGANESE FUME:

TOXICITY

Inhalation (man) TCl_o: 2.3 mg/m³

Oral (rat) LD₅₀: 9000 mg/kg

The substance has been investigated as a tumorigen;

found to be an equivocal tumorigenic agent by RTECS.

IRRITATION

Skin (rabbit) 500mg/24H Mild

Eye (rabbit) 500mg/24H Mild

MOLYBDENUM FUME:

No significant acute toxicological data identified in literature search.

IRON OXIDE FUME:

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

No oral toxicity data.

Substance has been investigated as a tumorigen;

found to be an equivocal tumorigenic agent by RTECS criteria.

CHROMIUM FUME:

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Not available.

COPPER FUME:

Not available. Refer to individual constituents.

OZONE:

TOXICITY

Inhalation (human) LCl_o: 50 ppm/30m

IRRITATION

Eye (rabbit): 2 ppm/4h

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 11 of 16

Section 11 - TOXICOLOGICAL INFORMATION

Inhalation (human) TClO: 1 ppm
Inhalation (rabbit) LC50: 36 ppm/3m
NOTE: Aggravates chronic obstructive pulmonary diseases. Suspected also of increasing the risk of acute and chronic respiratory disease, mutagenesis and fetotoxicity. In animals short-term exposure to ambient concentrations of less than 1 ppm results in reduced capacity to kill intrapulmonary organisms and allows purulent bacteria to proliferate [Ellenhorn etal]

NITROGEN OXIDES:

Data for nitrogen dioxide:

TOXICITY

IRRITATION

Inhalation (human) LClO: 200 ppm/1m

Nil reported

Inhalation (man) TClO: 6200 ppb/10m

Substance has been investigated as a mutagen and reproductive effector.

NOTE: Interstitial edema, epithelial proliferation and, in high concentrations, fibrosis and emphysema develop after repeated exposure.

MATERIAL	CARCINOGEN	REPROTOXIN	SENSITISER	SKIN
manganese fume		ILOM ILOEI		
iron oxide fume	IARC:Group 3			
chromium fume	IARC:Group 3			

REPROTOXIN

ILOM: ILO Agents toxic to the male reproductive system: manganese fume

REPROTOXIN

ILOEI: ILO Chemicals in the electronics industry that have toxic effects on reproduction: manganese fume

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: iron oxide fume
Category: Group 3: Not classifiable as to carcinogenicity to humans

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: chromium fume
Category: Group 3: Not classifiable as to carcinogenicity to humans

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.
Refer to data for ingredients, which follows:

COPPER FUME:

The material is classified as an ecotoxin* because the Fish LC50 (96 hours) is less than or equal to 0.1 mg/l

* Classification of Substances as Ecotoxic (Dangerous to the Environment)
Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993
Commission of the European Communities.

Copper is unlikely to accumulate in the atmosphere due to a short residence time for airborne copper aerosols. Airborne coppers, however, may be transported over large distances. Copper accumulates significantly in the food chain.

Drinking Water Standards:

3000 ug/l (UK max)

2000 ug/l (WHO provisional Guideline)

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 12 of 16

Section 12 - ECOLOGICAL INFORMATION

1000 ug/l (WHO level where individuals complain)

Soil Guidelines: Dutch Criteria

36 mg/kg (target)

190 mg/kg (intervention)

Air Quality Standards: no data available.

The toxic effect of copper in the aquatic biota depends on the bio-availability of copper in water which, in turn, depends on its physico-chemical form (ie.speciation). Bioavailability is decreased by complexation and adsorption of copper by natural organic matter, iron and manganese hydrated oxides, and chelating agents excreted by algae and other aquatic organisms. Toxicity is also affected by pH and hardness. Total copper is rarely useful as a predictor of toxicity. In natural sea water, more than 98% of copper is organically bound and in river waters a high percentage is often organically bound, but the actual percentage depends on the river water and its pH.

Copper exhibits significant toxicity in some aquatic organisms. Some algal species are very sensitive to copper with EC50 (96 hour) values as low as 47 ug/litre dissolved copper whilst for other algal species EC50 values of up to 481 ug/litre have been reported. However many of the reportedly high EC50 values may arise in experiments conducted with a culture media containing copper-complexing agents such as silicate, iron, manganese and EDTA which reduce bioavailability.

Toxic effects arising following exposure by aquatic species to copper are typically:

Algae EC50 (96 h)	Daphnia magna LC50 (48- 96 h)	Amphipods LC50 (48- 96 h)	Gastropods LC50 (48- 96 h)	Crab larvae LC50 (48- 96 h)
47- 481 *	7- 54 *	37- 183 *	58- 112 *	50- 100 *

* ug/litre

Exposure to concentrations ranging from one to a few hundred micrograms per litre has led to sublethal effects and effects on long-term survival. For high bioavailability waters, effect concentrations for several sensitive species may be below 10 ug Cu/litre.

In fish, the acute lethal concentration of copper ranges from a few ug/litre to several mg/litre, depending both on test species and exposure conditions. Where the value is less than 50 ug Cu/litre, test waters generally have a low dissolved organic carbon (DOC) level, low hardness and neutral to slightly acidic pH. Exposure to concentrations ranging from one to a few hundred micrograms per litre has led to sublethal effects and effects on long-term survival. Lower effect concentrations are generally associated with test waters of high bioavailability.

In summary:

Responses expected for high concentration ranges of copper *

Total dissolved Cu concentration range (ug/litre)
1- 10

Effects of high availability in water

Significant effects are expected for diatoms and sensitive invertebrates, notably cladocerans. Effects on fish could be significant in freshwaters with low pH and hardness.

10- 100

Significant effects are expected on various species of microalgae, some species of macroalgae, and a range of invertebrates, including crustaceans, gastropods and sea urchins. Survival of sensitive fish will be affected and a variety of fish show sublethal effects.

100- 1000

Most taxonomic groups of macroalgae and invertebrates will be severely affected. Lethal levels for most fish species will be reached.

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 13 of 16

Section 12 - ECOLOGICAL INFORMATION

>1000

Lethal concentrations for most tolerant organisms are reached.

* Sites chosen have moderate to high bioavailability similar to water used in most toxicity tests.

In soil, copper levels are raised by application of fertiliser, fungicides, from deposition of highway dusts and from urban, mining and industrial sources. Generally, vegetation rooted in soils reflects the soil copper levels in its foliage. This is dependent upon the bioavailability of copper and the physiological requirements of species concerned.

Typical foliar levels of copper are:

Uncontaminated soils (0.3- 250 mg/kg)	Contaminated soils (150- 450 mg/kg)	Mining/smelting soils
6.1- 25 mg/kg	80 mg/kg	300 mg/kg

Plants rarely show symptoms of toxicity or of adverse growth effects at normal soil concentrations of copper. Crops are often more sensitive to copper than the native flora, so protection levels for agricultural crops range from 25 mg Cu/kg to several hundred mg/kg, depending on country. Chronic and or acute effects on sensitive species occur at copper levels occurring in some soils as a result of human activities such as copper fertiliser addition, and addition of sludge.

When soil levels exceed 150 mg Cu/kg, native and agricultural species show chronic effects. Soils in the range 500-1000 mg Cu/kg act in a strongly selective fashion allowing the survival of only copper-tolerant species and strains. At 2000 Cu mg/kg most species cannot survive. By 3500 mg Cu/kg areas are largely devoid of vegetation cover. The organic content of the soil appears to be a key factor affecting the bioavailability of copper.

On normal forest soils, non-rooted plants such as mosses and lichens show higher copper concentrations. The fruiting bodies and mycorrhizal sheaths of soil fungi associated with higher plants in forests often accumulate copper to much higher levels than plants at the same site. International Programme on Chemical Safety (IPCS): Environmental Health Criteria 200.

OZONE:

The material is classified as an ecotoxin* because the Fish LC50 (96 hours) is less than or equal to 0.1 mg/l

* Classification of Substances as Ecotoxic (Dangerous to the Environment)

Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993

Commission of the European Communities.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

Air Transport IATA:

ICAO/IATA Class:

None

ICAO/IATA Subrisk:

None

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 14 of 16

Section 14 - TRANSPORTATION INFORMATION

UN/ID Number: None Packing Group: -
ERG Code: -
Shipping name:None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

welding fumes (CAS No:Not avail):
No regulations applicable

manganese fume (CAS: 7439-96-5) is found on the following regulatory lists;
Australia - Australian Capital Territory Environment Protection Regulation
Agricultural Uses (IRRIG) - Physical and chemical quality
Australia - Australian Capital Territory Environment Protection Regulation
water quality standards - Inorganic chemicals
Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Irrig)
Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Domestic water quality
Australia Exposure Standards
Australia Inventory of Chemical Substances (AICS)
Australia National Pollutant Inventory
OECD Representative List of High Production Volume (HPV) Chemicals
WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are
of health significance in drinking-water

Domesti

molybdenum fume (CAS: 7439-98-7) is found on the following regulatory lists;
Australia - Australia New Zealand Food Standards Code - Processing Aids - Permitted
catalysts
Australia - Australian Capital Territory Environment Protection Regulation
Agricultural Uses (IRRIG) - Physical and chemical quality
Australia - Australian Capital Territory Environment Protection Regulation
Agricultural uses (STOCK) - Physical and chemical quality
Australia - Australian Capital Territory Environment Protection Regulation
water quality standards - Inorganic chemicals
Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Irrig)
Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Stock)
Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Domestic water quality
Australia Exposure Standards
Australia Inventory of Chemical Substances (AICS)
OECD Representative List of High Production Volume (HPV) Chemicals
WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are
of health significance in drinking-water

Domesti

iron oxide fume (CAS: 1309-37-1) is found on the following regulatory lists;
Australia Exposure Standards
Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 15 of 16

Section 15 - REGULATORY INFORMATION

International Agency for Research on Cancer (IARC) Carcinogens
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

chromium fume (CAS: 7440-47-3) is found on the following regulatory lists;

Australia - Australia New Zealand Food Standards Code - Processing Aids - Permitted catalysts

Australia - Australian Capital Territory Environment Protection Regulation
Agricultural Uses (IRRIG) - Physical and chemical quality

Australia - Australian Capital Territory Environment Protection Regulation
Agricultural uses (STOCK) - Physical and chemical quality

Australia - Australian Capital Territory Environment Protection Regulation
maintenance - Inorganic chemicals

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Irrig)

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Stock)

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Domestic water quality

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Ecosystem maintenance

Australia - Western Australia Hazardous Substances Prohibited for Specified Uses or
Methods of Handling

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia National Pollutant Inventory

International Agency for Research on Cancer (IARC) Carcinogens

OECD Representative List of High Production Volume (HPV) Chemicals

WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are
of health significance in drinking-water

copper fume (CAS: 7440-50-8) is found on the following regulatory lists;

Australia - Australia New Zealand Food Standards Code - Processing Aids - Permitted catalysts

Australia - Australian Capital Territory Environment Protection Regulation
Agricultural Uses (IRRIG) - Physical and chemical quality

Australia - Australian Capital Territory Environment Protection Regulation
Agricultural uses (STOCK) - Physical and chemical quality

Australia - Australian Capital Territory Environment Protection Regulation
water quality standards - Inorganic chemicals

Australia - Australian Capital Territory Environment Protection Regulation
maintenance - Inorganic chemicals

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Irrig)

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Agricultural uses (Stock)

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Domestic water quality

Australia - Australian Capital Territory Environment Protection Regulation
Pollutants entering waterways - Ecosystem maintenance

Australia Dangerous Goods Code Draft 7th Edition - List of Common Pesticides with
Corresponding UN Numbers

Australia Exposure Standards

Australia High Volume Industrial Chemical List (HVICL)

Australia Inventory of Chemical Substances (AICS)

Australia National Pollutant Inventory

OECD Representative List of High Production Volume (HPV) Chemicals

WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are

continued...

CIGWELD COMWELD CRMO1, COMWELD CRMO2

Chemwatch Material Safety Data Sheet

Issue Date: 31-Oct-2006

NC317ECP

CHEMWATCH 46931

Revision No:2

CD 2006/3 Page 16 of 16

Section 15 - REGULATORY INFORMATION

of health significance in drinking-water

ozone (CAS: 10028-15-6) is found on the following regulatory lists;

Australia - Australia New Zealand Food Standards Code - Processing Aids - Permitted bleaching agents, washing and peeling agents and in water used as an ingredient in other foods

Australia - Australia New Zealand Food Standards Code - Processing Aids - Permitted processing aids used in packaged water and in water used as an ingredient in other foods

Australia Exposure Standards

No data available for welding fumes as CAS: Not avail.

No data available for nitrogen oxides as CAS: Mixture.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
carbon, non-activated	7440- 44- 0, 82600- 58- 6

EXPOSURE STANDARD FOR MIXTURES

46931

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m³): 6 mg/m³

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc: (%).

Component	Breathing zone (ppm)	Breathing Zone (mg/m ³)	Mixture Conc (%)
nitrogen oxides	3.00	6.0000	0.1

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 31-Oct-2006

Print Date: 31-Oct-2006