

**CABLE SPLICERS**




**TS-3040**

(MODEL NO. / STOCK NO.)	Description	Welding Cable Size	Tube I.D.	Standard Package
<b>TS-62-50</b> 9610-1105	Copper Splicer	6 thru 2	.461" 11,7mm	50
<b>TS-62</b> 9610-1101	Copper Splicer	6 thru 2	.461" 11,7mm	5
<b>TS-120-50</b> 9610-1106	Copper Splicer	1 thru 2/0	.599" 15,2mm	50
<b>TS-120</b> 9610-1102	Copper Splicer	1 thru 2/0	.599" 15,2mm	5
<b>TS-3040-25</b> 9610-1107	Copper Splicer	3/0 thru 4.0	.660" 16,8mm	25
<b>TS-3040</b> 9610-1103	Copper Splicer	3/0 thru 4.0	.660" 16,8mm	5
<b>TS-40HD-24</b> 9610-1108	Copper Splicer	4/0 Heavy-Duty	.776" 19,7mm	24
<b>TS-40HD</b> 9610-1104	Copper Splicer	4/0 Heavy-Duty	.776" 19,7mm	5

**TWECO® “LUG-SET” BLOCK & PUNCH**

For Use With Twecolugs



**12-BP**

(MODEL NO. / STOCK NO.)	Description
<b>12-BP</b> 9900-1140	Block & Punch

**JACKET STRIPPING CABLE CUTTING HAND TOOL**



**T-908**

(MODEL NO. / STOCK NO.)	Description
<b>T-908</b> 9900-1190	Tweco Cable Cutting Hand Tool

**TWECO SHAFT LUBRICANT**

An electrical conductive grease to be used as a lubricant for roto-grounds and may be used when making mechanical connections with copper or aluminum cables. Effective as a lubricant on sliding or moving electrical contacts such as switches and rotating grounding devices. Apply generously to contact area from 1 oz. (29,6ml) or 8 oz. (237,0ml) plastic squeeze bottles. Reduce electrical resistance by as much as 40 to 50%



**5B-L**

**8Z-L**

**1Z-L**

(MODEL NO. / STOCK NO.)	Description
<b>1Z-L</b> 9900-1123	Tweco Shaft Lubricant, 1 oz. (29,6ml) Plastic Squeeze Bottle
<b>8Z-L</b> 9900-1124	Tweco Shaft Lubricant, 8 oz. (237,0ml) Plastic Squeeze Bottle
<b>5B-L</b> 9900-1125	Tweco Shaft Lubricant, 5 lb. (2,3kg) Jar