

Automated Metal-Removal System Accessories

Arcair
Professional

CLIMBER® V-A TRACTOR

- Positive-locking gear engagement lever.
- Hardened drive gear to reduce maintenance.
- Solid state circuitry.
- Manual or Automatic Control. (Automatic control synchronizes the process and tractor motion.)
- Powered by a permanent magnet DC parallel shaft gear-motor, lubricated for life.

Climber® V-A Tractor

Packages includes: Climber V-A Tractor, Track Assembly (10ft./3M Long), Magnet Assemblies (5), Horizontal Rack Assembly, Vertical Adjustment Assembly, Cable Hose Clamp Assembly, and Mounting Plate Assembly.

A complete assembly for mounting on ferrous materials. This package gives portability and flexibility for out-of-position work.



CLIMBER® V-A TRACTOR PACKAGE

Description	(PART NO.)	
	Tractor Only	Tractor Package
120 VAC, 60 Hz 0-100 ipm (0-254 cm/min)	71-023-136	71-023-138
220 VAC, 50 Hz 0-100 ipm (0-254 cm/min)	71-023-137	71-023-139
Aluminum Track Section (3'/1M Length)	71-099-003	71-099-003
Aluminum Track Section (6'/2M Length)	71-099-002	71-099-002
Aluminum Track Section (10'/3M Length)	71-099-001	71-099-001
Magnet and Support Bar Assembly	71-099-004	71-099-004

NOTE: When using the travel system in the vertical, horizontal, and overhead positions, use of safety attachments is recommended to prevent operator injury or equipment damage.

NOTE: The Climber® V-A Package will carry the N6000 Torch Head and Automatic Controller. When mounting the Automatic Controller on the Climber V-A, choose the 3 ft. Motor Cable Assembly (Catalog No. 96-130-257).

TITAN® MACHINE CARRIAGE

The Arcair® Titan® Machine Carriage is designed for low maintenance and high performance in straight line operation, such as automated air carbon arc gouging, cutting or welding operations. Its three wheel design ensures maximum stability even on warped plates. The machine carriage is available in a speed range from 6-80 IPM (15,2-203,2 cm/min.). A manually operated clutch allows the drive to be disengaged for free wheeling to the start of the next operation.



TITAN® MACHINE CARRIAGE

Description	(PART NO.)
	Arcair
120 VAC, 60 Hz 6-80 ipm (15,2-203,2 cm/min)	71-022-501
Track Assembly (10'/3M Length)	71-022-502
Magnet and Support Bar Assembly (3 Required/Track Assembly)	71-022-504

U.S. Customer Care: 800-426-1888 / FAX 800-535-0557