

Eliminator® Pull Gun

Tweco's new 300 Amp Eliminator® Pull Gun is available with 15', 25' or 50' cable lengths.

The Pull Gun runs 300 amps at 60% duty cycle with mixed gases with a wire feed range of 900 inches per minute. To ensure smooth wire feed, we've added self-centering wire guides and drive rolls for .030" (0,8mm)- 1/16" (1,6mm) wire. The Eliminator® Pull Gun utilizes feeder speed control.

Teflon conduits are standard with the Pull Gun to enhance the quality of your welds. We've provided repairable cable connections and spring Cablehoz® support to extend the life of your Pull Gun and keep your maintenance down.



300 AMP ELIMINATOR PULL GUN

Most of all, we think you'll like the lightweight design of the Eliminator® Pull Gun. It weighs 2.32 lbs.

- **Comfortable Handle Design**
- **Uses Long-Life Eliminator® Consumables**
- **Quick Disconnect Conductor Tube**
- **180° Conductor Tube Standard with Optional 45° Tube which Swivels 360°**
- **180° Conductor Tubes Available in 4" and 6" Lengths**

- **Conductor Tube has a Copper Jumper Liner to Assist with Arc Start**
- **Tweco's Eliminator® Pull Gun fits most welding machines with the use of our EPG-CR1 or EPG-CR2 control box**

COMPLETE GUN ASSEMBLIES With 24 Volt Motors

Description	Eliminator Pull Gun (PART NO. / STOCK NO.)	
	Tweco*	Euro-Kwik
Gun Assembly with 15' (5M) Cable	EPG215T-3545 1027-1320	N/A
Gun Assembly with 25' (8M) Cable	EPG225T-3545 1027-1321	EPG225X-3545 1027-1346
Gun Assembly with 50' (15M) Cable	EPG250T-3545 1027-1323	EPG250X-3545 1027-1348

* Requires EPG-CR1 or EPG-CR2 Control Box

NOTE: Gun Assemblies with Tweco rear connections are shipped with a Miller® and Lincoln® plug.

CONTROL BOX - Used to connect Pull Gun to most welding machines

Description	Eliminator Control Box (PART NO. / STOCK NO.)	
	Tweco	
Control Box with Pre & Post Purge Gas Control	EPG-CR2 1028-1291	

Control Box



EPG-CR2