

HEAVY-DUTY TYPE LUGS

Mechanical Ball-Point


(MODEL NO. / STOCK NO.)

	Description	Cable Capacity	Size Of Stud Hole	English Package	Metric Length
140-HD-180 9515-1120	180° Offset	3/0 & 4/0	21/32" 16,7mm	4 3/8"	111mm
140-HD-180C 9515-1121	With Insulated Cover - 180° Offset	3/0 & 4/0	21/32" 16,7mm	5 1/2"	140mm
240-HD-180 9515-1122	180° Offset	3/0 & 4/0	21/32" 16,7mm	4 5/8"	131mm

TWECO® CABLE SPLICERS

Ball-Point Type

(MODEL NO. / STOCK NO.)



BP-1030

	Cable Fitting Type	Cable Capacity	Standard Package
BP-410-12 9605-1102	Ball Point	4, 2, 1, 1/0	12
BP-410 9605-1101	Ball Point	4, 2, 1, 1/0	1
BP-1030-12 9605-1104	Ball Point	1/0, 2/0, 3/0	12
BP-1030 9605-1103	Ball Point	1/0, 2/0, 3/0	1
BP-2040-6 9605-1106	Ball Point	2/0, 3/0, 4/0	6
BP-2040 9605-1105	Double Ball Point	2/0, 3/0, 4/0	1

PANEL RECEPTACLES

Use With MPC Connectors

(MODEL NO. / STOCK NO.)



238-TSF

2916-BPF

	Cable Fitting Type	Fits Tweco Connector	For Cable Size	Cable Attachment
1516-BPF 9580-1100	Ball-Point	No. 1	4, 2, 1	5/16" Ball-Point 7,9mm
114-TSF 9580-1101	Threaded	No. 1	4, 2, 1, 1/0	5/16" Thread, Stud 7,9mm
238-TSF 9580-1102	Threaded	No. 2, 4	1/0, 2/0, 3/0	3/8" Thread, Stud 9,5mm
2916-BPF 9580-1103	Ball-Point	No. 2, 4	1/0, 2/0, 3/0	9/16" Ball-Point 14,3mm
212-TSF 9580-1104	Threaded	No. 2, 4	1/0, 2/0, 3/0	1/2" - 20 Thread, Stud 12,7mm