



REL24CT-75



REL24CT-62F

QRA Air-cooled Nozzles

REL22CT Nozzle – Standard Tip Recess – .125" to .156" (3,18mm to 3,96mm)

Bore Size	Part No.	Stock No.	A	B	C	D
.375"- 9,5mm	REL22CT-37	1220-1250	.395"/10,03mm	.545"/13.84mm	.943"/23.96mm	.875"/22,23mm
.500"-12,7mm	REL22CT-50	1220-1255	.520"/13,21mm	.670"/17,02mm	1.05"/26,71mm	.875"/22,23mm
.625"-15,9mm	REL22CT-62	1220-1260	.645"/16,38mm	.795"/20,19mm	1.16"/29,46mm	.875"/22,23mm

REL22CT Nozzle – Flush Tip Recess – Flush to .062" (1,57mm)

Bore Size	Part No.	Stock No.	A	B	C	D
.375"- 9,5mm	REL22CT-37F	1220-1251	.395"/10,03mm	.545"/13.84mm	.834"/10,03mm	.875"/22,23mm
.500"-12,7mm	REL22CT-50F	1220-1256	.520"/13,21mm	.670"/17,02mm	.942"/23,94mm	.875"/22,23mm
.625"-15,9mm	REL22CT-62F	1220-1261	.645"/16,38mm	.795"/20,19mm	1.05"/26,71mm	.875"/22,23mm

REL22CT Nozzle – Protruding Tip – .125" to .187" (3,18mm to 4,75mm)

Bore Size	Part No.	Stock No.	A	B	C	D
.375"- 9,5mm	REL22CT-37P	1220-1252	.395"/10,03mm	.545"/13.84mm	.647"/16,44mm	.875"/22,23mm
.500"-12,7mm	REL22CT-50P	1220-1257	.520"/13,21mm	.670"/17,02mm	.755"/19,19mm	.875"/22,23mm
.625"-15,9mm	REL22CT-62P	1220-1262	.645"/16,38mm	.795"/20,19mm	.864"/21,94mm	.875"/22,23mm

REL24CT Nozzle – Standard Tip Recess – .125" to .156" (3,18mm to 3,96mm)

Bore Size	Part No.	Stock No.	A	B	C	D
.500"-12,7mm	REL24CT-50	1240-1305	.520"/13,21mm	.670"/17,02mm	.882"/22,4mm	1.00"/25,4mm
.625"-15,9mm	REL24CT-62	1240-1306	.645"/16,38mm	.790"/20,1mm	.952"/24,19mm	1.00"/25,4mm
.750"-19,1mm	REL24CT-75	1240-1307	.770"/19,56mm	.920"/23,2mm	1.03"/26,16mm	1.00"/25,4mm

REL24CT Nozzle – Flush Tip Recess – Flush to .062" (1,57mm)

Bore Size	Part No.	Stock No.	A	B	C	D
.500"-12,7mm	REL24CT-50F	1240-1315	.520"/13,21mm	.670"/17,02mm	.772"/19,61mm	1.00"/25,4mm
.625"-15,9mm	REL24CT-62F	1240-1316	.645"/16,38mm	.790"/20,1mm	.842"/21,4mm	1.00"/25,4mm
.625"-15,9mm	REL24CT-62FL	1240-1318	.645"/16,38mm	.790"/20,1mm	1.55"/39,48mm	1.00"/25,4mm
.750"-19,1mm	REL24CT-75F	1240-1317	.770"/19,56mm	.920"/23,2mm	.916"/23,7mm	1.00"/25,4mm

REL24CT Nozzle – Protruding Tip – .125" to .187" (3,18mm to 4,75mm)

Bore Size	Part No.	Stock No.	A	B	C	D
.500"-12,7mm	REL24CT-50P	1240-1310	.520"/13,21mm	.670"/17,02mm	.585"/14,86mm	1.00"/25,4mm
.625"-15,9mm	REL24CT-62P	1240-1311	.645"/16,38mm	.790"/20,1mm	.655"/16,65mm	1.00"/25,4mm
.750"-19,1mm	REL24CT-75P	1240-1312	.770"/19,56mm	.920"/23,2mm	.729"/18,52mm	1.00"/25,4mm

